

PVC Reinforced membrane · KOLOS



Delos 1,65m · 35116103
2,05m · 35116104




Zephir 1,65m · 35116101
2,05m · 35116102



RecyClass **40%**
RECYCLED
PLASTIC

Packaging



78.4 kg/roll (1.65m)
95.6 kg/roll (2.05m)

Rolls must be stored **horizontally** in the **original packaging**, in a **dry environment** and at moderate ambient temperature (**15–25°C**)

PVC Seam Sealer



6 units/box
900gr/unit

Delos 81056002
Zephir 81056001

Geotextile



Raw material: Polypropylene
400 gr/m² · Light Blue

1.5mm thickness – 6 rolls/pallets

81006005* | 1,5m x 50m

81006006 | 1,65m x 50m

81006007 | 2m x 50m

* Specifically for butt welding.

Butt Weld Backing Strip



Colour: Dark Grey

81113T20 15cm x 20m | 1.5mm thickness

TECHNICAL SPECIFICATIONS

Slip resistance



Class C (≥ 24°)
under DIN-EN 16165 A



Pendulum Test
This collection has the **highest anti-slip certification**, to ensure safety inside the water.
Class 3 (>45°)
under UNE-EN 16165 C



Passes ANSI A326.3
(≥0,42)

Security



Security membranes
under EN71-3 safety for toys.

Temperature



Water Max Temperature
The maximum temperature recommended
for this collection is 35° Celsius.

Guarantee



Guarantee
20 years of Watertightness.



Guarantee
5 years of Anti-stain.