



PVC Reinforced membrane · TOUCH

		
Elegance 35517701	Prestige 35517603	Origin 35517613
		
Vanity 35517609	Relax 35517601	Sublime 35517607
		
Authentic 35517602	RecyClass 17% RECYCLED PLASTIC	

Packaging

25m
1.65m

8 rolls

97 kg/roll

Rolls must be stored horizontally in the original packaging, in a dry environment and at moderate ambient temperature (15-25°C)

PVC Seam Sealer

	6 units/box 900gr/unit	Elegance 81023001 Prestige 81023006 Origin 81023007 Vanity 81023004 Relax 81023002 Sublime 81023005 Authentic 81023003
--	---------------------------	--

Geotextile



Raw material: Polypropylene
400 gr/m² · Light Blue
1.5mm thickness – 6 rolls/pallets

81006005* | 1,5m x 50m
81006006 | 1,65m x 50m
81006007 | 2m x 50m

* Specifically for butt welding.

Butt Weld Backing Strip



Colour: Dark Grey
81113T20 15cm x 20m | 1.5mm thickness

TECHNICAL SPECIFICATIONS

Slip resistance



Class C (≥ 24°)
under DIN-EN 16165 A



Pendulum Test
This collection has the highest anti-slip certification, to ensure safety inside the water.
Class 3 (>45°)
under UNE-EN 16165 C



Passes ANSI A326.3
(≥0,42)

Security



Security membranes
under EN71-3 safety for toys.

Temperature



Water Max Temperature
The maximum temperature recommended for this collection is 35° Celsius.

Guarantee



Guarantee
15 years of Watertightness.



Guarantee
3 years of Anti-stain.